



Fair Winds Boat Repairs

134 Riberia Street #7
32084 St. Augustine
Tel : 904-669-6045
Fax :



Cadet Compact 300

Model Overview:

Thanks to its fold-down rear transom – exclusive to ZODIAC™ – the boat takes up very little space once deflated and can be simply stored in the specially designed bag. This bag, with integrated handles, enables you to carry your boat in the simplest way possible – on the roof of your car or in a large boot. Setting up the boat is extremely rapid: simply inflate it, fit the oars and launch it!

Very light thanks to its RIMTEC (**Reinforced Injection Moulding Technology**) manufacturing process, its hull makes it comfortable and stable as well as providing excellent handling on the water. The large hollow interior allows a perfectly ergonomic seating position whilst also improving safety.

Plus Products:

- Progressive-diameter buoyancy tube
- Stores flat in a bag
- Ease of carrying, storage and set up
- Comfort on the water

Item code:

Fabric:

Colour:

Floor:

Specifications

Dimensions (m - fi)

Length overall:	3.00 - 9'10"
Inside length:	2.02 - 6'8"
Width overall:	1.62 - 5'4"
Inside width:	0.70 - 2'4"
Tube diametre:	0.45 - 1'6"

Capacity

Passengers (ISO):	4
Max payload allowed (B) (kg - lbs):	-
Max payload allowed (C) (kg - lbs):	450 - 992
Total weight (kg - lbs):	48 - 106
Airtight compartments:	2

Outboard data

Shaft	Short
Min recommended power (Hp - kW):	6 - 5
Max recommended power (Hp - kW):	8 - 6
Max power allowed (Hp - kW):	10 - 8
Max speed (km/h - mph):	34 - 21

Category

European directive	C
--------------------	---

Hull storage (m - fi)

Length:	2.16 - 7'1"	Height:	0.30 - 1'0"
Width:	0.90 - 2'11"	Hull angle (°):	-

Folded boat dimensions (m - fi)

Length of 1st bag:	-	Length of 2nd bag:	-
Width of 1st bag:	-	Width of 2nd bag:	-
Height of 1st bag:	-	Height of 2nd bag:	-

Equipments

Hull

- V-shaped Rimtec hull
- Moulded non-slip deck
- Marine-ply folding transom
- 1 Bow D-ring
- 3 lifting points
- Fuel tank securing system
- Aluminium engine mounting plate
- 1 bailer

Buoyancy tube

- Strongan™ fabric
- Easy Push valves
- Handrail
- 2 Swivel oarlocks
- Broad rubbing strip
- 1 Bow handle
- 2 oar rests
- 2 stainless steel tow rings
- 2 carrying handles
- Cone reinforcers

Standard Equipment

- Transportation cover
- "Quick Release" removable thwart (dual position)
- Reinforced aluminium oars + oarlock with locking ring
- Foot pump
- Repair kit
- Owner's manual