



### Fair Winds Boat Repairs

134 Riberia Street #7  
32084 St. Augustine  
Tel : 904-669-6045  
Fax :



## Cadet Fastroller 325

### Model Overview:

Compact, boasting unequalled load-capacity, tough yet elegant, the CADET FASTROLLER range represents the very best of tenders. Its Acti-V hull provides improved performance without the need for a more powerful motor. Its anti-drift fins provide excellent control and crisp and accurate handling.

The CADET FASTROLLER comes as standard with a removable quick-mounting thwart, "safe-clic" oarlocks, an internally-operated bailer plus optional flaps that improve handling by enabling the boat to plane quickly but without rearing. Thanks to ZODIAC™ technology's H2P concept, the boat is quick to assemble and can be easily stowed in a bag. This feature also provides the hull with increased rigidity that significantly improves performance. The banana-shaped buoyancy tube gives it an elegant and streamlined look.

### Plus Products:

- Superior seating space
- Large diameter half-banana-shaped buoyancy tube: greater stability and safety
- Quick assembly
- Handling and comfort on the water
- V-hull
- Rigid inflatable keel

Item code:

Fabric:

Colour:

Floor:

# Specifications

## Dimensions (m - fi)

Length overall:	3.25 - 10'8"
Inside length:	2.29 - 7'6"
Width overall:	1.68 - 5'6"
Inside width:	0.78 - 2'7"
Tube diametre:	0.45 - 1'6"

## Capacity

Passengers (ISO):	5
Max payload allowed (B) (kg - lbs):	-
Max payload allowed (C) (kg - lbs):	490 - 1080
Total weight (kg - lbs):	38 - 84
Airtight compartments:	3 + 1

## Outboard data

Shaft	Short
Min recommended power (Hp - kW):	4 - 3
Max recommended power (Hp - kW):	8 - 6
Max power allowed (Hp - kW):	10 - 8
Max speed (km/h - mph):	37 - 23

## Category

European directive	C
--------------------	---

## Hull storage (m - fi)

Length:	-	Height:	-
Width:	-	Hull angle (°):	-

## Folded boat dimensions (m - fi)

Length of 1st bag:	1.15 - 3'9"	Length of 2nd bag:	-
Width of 1st bag:	0.60 - 2'0"	Width of 2nd bag:	-
Height of 1st bag:	0.40 - 1'4"	Height of 2nd bag:	-

# Equipments

## Hull

- H2P (high pressure performance) removable inflatable floor
- H2P inflatable keel
- Anti-drift fins
- Aluminium engine mounting plate
- 1 internally-operated bailer

## Buoyancy tube

- Strongan™ fabric
- Easy Push valves
- Handrail
- 2 oar rests
- 2 "Safe Clic" swivel oarlocks
- All-round ribbed rubbing strip (width: 125 mm)
- 1 bow handle
- 2 stainless steel lifting rings
- 2 stainless steel tow rings
- 2 carrying handles
- Cone reinforcers

## Standard Equipment

- "Quick Release" removable thwart (dual position)
- Fuel tank strap
- Reinforced aluminium oars + oarlock with locking ring
- "Modulo" carrying bag
- High pressure foot pump + pressure indicator
- Repair kit
- Owner's manual