



### Fair Winds Boat Repairs

134 Riberia Street #7  
32084 St. Augustine  
Tel : 904-669-6045  
Fax :



## Cadet Fastroller NEO 325

### Model Overview:

The CADET FASTROLLER NEO combines all the qualities of the classic CADET FASTROLLER with those of its Hypalon™-Neoprene fabric™.

Its rapidly assembled high pressure inflatable floor and Acti-V hull offer comfortable handling and greatly improve performance of the vessel and its engine. Control is easier thanks to its anti-drift fins.

The elegant and stylish lines of its banana-shaped buoyancy tube, made of Hypalon™-Neoprene™ fabric, offers excellent resistance to extreme conditions (tropical areas, frequent use, etc.). Being more flexible, this boat may be easily folded into its bag.

### Plus Products:

- Hypalon™-Neoprene™ fabric
- Superior seating space
- Large diameter half-banana-shaped buoyancy tube: greater stability and safety
- Quick assembly
- Handling and comfort on the water
- V-hull
- Rigid inflatable keel

Item code:

Fabric:

Colour:

Floor: FR

# Specifications

## Dimensions (m - fi)

|                 |              |
|-----------------|--------------|
| Length overall: | 3.25 - 10'8" |
| Inside length:  | 2.29 - 7'6"  |
| Width overall:  | 1.68 - 5'6"  |
| Inside width:   | 0.78 - 2'7"  |
| Tube diametre:  | 0.45 - 1'6"  |

## Capacity

|                                     |            |
|-------------------------------------|------------|
| Passengers (ISO):                   | 5          |
| Max payload allowed (B) (kg - lbs): | -          |
| Max payload allowed (C) (kg - lbs): | 490 - 1080 |
| Total weight (kg - lbs):            | 38 - 84    |
| Airtight compartments:              | 3 + 1      |

## Outboard data

|                                  |         |
|----------------------------------|---------|
| Shaft                            | Short   |
| Min recommended power (Hp - kW): | 4 - 3   |
| Max recommended power (Hp - kW): | 8 - 6   |
| Max power allowed (Hp - kW):     | 10 - 8  |
| Max speed (km/h - mph):          | 37 - 23 |

## Category

|                    |   |
|--------------------|---|
| European directive | C |
|--------------------|---|

## Hull storage (m - fi)

|         |   |                 |   |
|---------|---|-----------------|---|
| Length: | - | Height:         | - |
| Width:  | - | Hull angle (°): | - |

## Folded boat dimensions (m - fi)

|                    |             |                    |   |
|--------------------|-------------|--------------------|---|
| Length of 1st bag: | 1.15 - 3'9" | Length of 2nd bag: | - |
| Width of 1st bag:  | 0.60 - 2'0" | Width of 2nd bag:  | - |
| Height of 1st bag: | 0.40 - 1'4" | Height of 2nd bag: | - |

# Equipments

## Hull

- H2P (high pressure performance) removable inflatable floor
- H2P inflatable keel
- Anti-drift fins
- Aluminium engine mounting plate
- 1 internally-operated bailer

## Buoyancy tube

- Hypalon™- Neoprene™ fabric
- Easy Push valves
- Handrail with fabric handles
- 2 oar rests
- 2 "Safe Clic" swivel oarlocks
- All-round ribbed rubbing strip (width: 125 mm)
- 1 bow handle
- 2 stainless steel lifting rings
- 2 stainless steel tow rings
- 2 carrying handles
- Cone reinforcers

## Standard Equipment

- "Quick Release" removable thwart (dual position)
- Fuel tank strap
- Reinforced aluminium oars + oarlock with locking ring
- "Modulo" carrying bag
- High pressure foot pump + pressure indicator
- Repair kit
- Owner's manual