



Fair Winds Boat Repairs

134 Riberia Street #7
32084 St. Augustine
Tel : 904-669-6045
Fax :



Cadet RIB 220

Model Overview:

The tapering buoyancy tubes, which are wider at the stern, make these RIB tenders better suited to the more reliable and easy to use four-stroke motors. The additional buoyancy associated with a padded* hull, provides the CADET Rib with an impressive load capacity 50% higher than that for a traditional tender. The wide diameter of its truncated-cone buoyancy tube ensures surprising stability, making it easy to steer, even in choppy seas. Its generous seating, flat deck (enabling a console to be fitted on the 310, 340 and 400 models) as well as the bow storage locker* make it uniquely comfortable, plus very easy to board and disembark.

*Only on CADET 310 Rib & 400 Rib

Plus Products:

- Progressive diameter buoyancy tubes
- Integrated lifting points
- Moulded non-slip deck
- Excellent performance on the water

Item code:

Fabric:

Colour:

Floor:

Specifications

Dimensions (m - fi)

Length overall:	2.20 - 7'3"
Inside length:	1.30 - 4'3"
Width overall:	1.39 - 4'7"
Inside width:	0.58 - 1'11"
Tube diametre:	0.40 - 1'4"

Capacity

Passengers (ISO):	2
Max payload allowed (B) (kg - lbs):	-
Max payload allowed (C) (kg - lbs):	260 - 573
Total weight (kg - lbs):	31 - 68
Airtight compartments:	2

Outboard data

Shaft	Short
Min recommended power (Hp - kW):	3 - 2
Max recommended power (Hp - kW):	4 - 3
Max power allowed (Hp - kW):	4 - 3
Max speed (km/h - mph):	16 - 10

Category

European directive	-
--------------------	---

Hull storage (m - fi)

Length:	1.70 - 5'7"	Height:	0.40 - 1'4"
Width:	0.85 - 2'9"	Hull angle (°):	18.0

Folded boat dimensions (m - fi)

Length of 1st bag:	-	Length of 2nd bag:	-
Width of 1st bag:	-	Width of 2nd bag:	-
Height of 1st bag:	-	Height of 2nd bag:	-

Equipments

Hull

- V-shaped polyester hull
- Moulded non-slip deck
- 1 bow D-ring
- 3 integral lifting points
- Aluminium engine mounting plate
- 1 bailer

Buoyancy tube

- Strongan™ fabric
- Easy Push valves
- Handrail
- 2 Swivel oarlocks
- 2 oar rests
- 2 stainless steel tow rings
- Cone reinforcers

Standard Equipment

- Reinforced aluminium oars + oarlock with locking ring
- Foot pump
- Repair kit
- Owner's manual