



Fair Winds Boat Repairs

134 Riberia Street #7 32084 St. Augustine Tel: 904-669-6045

Fax:



Cadet RIB 260

Model Overview:

The tapering buoyancy tubes, which are wider at the stern, make these RIB tenders better suited to the more reliable and easy to use four-stroke motors. The additional buoyancy associated with a padded* hull, provides the CADET Rib with an impressive load capacity 50% higher than that for a traditional tender. The wide diameter of its truncated-cone buoyancy tube ensures surprising stability, making it easy to steer, even in choppy seas. Its generous seating, flat deck (enabling a console to be fitted on the 310, 340 and 400 models) as well as the bow storage locker* make it uniquely comfortable, plus very easy to board and disembark.

*Only on CADET 310 Rib & 400 Rib

Plus Products:

- Progressive diameter buoyancy tubes
- Integrated lifting points
- Moulded non-slip deck
- Excellent performance on the water

Item code:

Fabric:

Colour:

Floor:

Specifications

Dimensions (m - fi)		Capacity	
Length overall:	2.60 - 8'6"	Passengers (ISO):	3
Inside length:	1.75 - 5'9"	Max payload allowed (B) (kg - lbs):	-
Width overall:	1.62 - 5'4"	Max payload allowed (C) (kg - lbs):	329 - 725
Inside width:	0.70 - 2'4"	Total weight (kg - lbs):	50 - 110
Tube diametre:	0.45 - 1'6"	Airtight compartments:	2
Outboard data		Category	
Shaft	Short	European directive	D
Min recommended power (Hp - kW):	4 - 3		
Max recommended power (Hp - kW):	8 - 6		
Max power allowed (Hp - kW):	8 - 6		
Max speed (km/h - mph):	31 - 19		
Hull storage (m - fi)			
Length:	2.05 - 6'9"	Height:	0.42 - 1'5
Width:	0.86 - 2'10"	Hull angle (°):	16.0
Folded boat dimensions (m - fi)			
Length of 1st bag:	-	Length of 2nd bag:	-
Width of 1st bag:	-	Width of 2nd bag:	-
Height of 1st bag:	-	Height of 2nd bag:	-

Equipments

	Hull	Buoyancy tube
--	------	---------------

 V-shaped polyester hull 	 Strongan™ fabric
 Moulded non-slip deck 	 Easy Push valves
• 1 bow D-ring	 Handrail
3 integrated lifting points	 2 Swivel oarlocks
 Fuel tank securing system 	 Broad rubbing strip
 Aluminium engine mounting plate 	2 oar rests
1 bailer	 2 stainless steel tow rings
	 2 carrying handles
	Cone reinforcers

Standard Equipment

- "Quick Release" upholstered removable thwart
- Reinforced aluminium oars + oarlock with locking ring
- Foot pump
- Repair kit
- Owner's manual