Model leaflet: Cadet RIB 400



$\mathbf{\tilde{\mathbf{v}}}$

Fair Winds Boat Repairs

134 Riberia Street #7 32084 St. Augustine Tel : 904-669-6045 Fax :



Cadet RIB 400

Model Overview:

The tapering buoyancy tubes, which are wider at the stern, make these RIB tenders better suited to the more reliable and easy to use four-stroke motors. The additional buoyancy associated with a padded* hull, provides the CADET Rib with an impressive load capacity 50% higher than that for a traditional tender. The wide diameter of its truncated-cone buoyancy tube ensures surprising stability, making it easy to steer, even in choppy seas. Its generous seating, flat deck (enabling a console to be fitted on the 310, 340 and 400 models) as well as the bow storage locker* make it uniquely comfortable, plus very easy to board and disembark.

*Only on CADET 310 Rib & 400 Rib

Plus Products:

- Progressive diameter buoyancy tubes
- Integrated lifting points
- Moulded non-slip deck
- · Excellent performance on the water

Item code: Fabric: Colour: Floor:

Specifications

Dimensions (m - fi)		Capacity	
Length overall:	4.00 - 13'1"	Passengers (ISO):	7
Inside length:	2.90 - 9'6"	Max payload allowed (B) (kg - lbs):	-
Width overall:	1.95 - 6'5"	Max payload allowed (C) (kg - lbs):	780 - 1720
Inside width:	0.95 - 3'1"	Total weight (kg - lbs):	165 - 364
Tube diametre:	0.50 - 1'8"	Airtight compartments:	3
Outboard data		Category	
Shaft	Long	European directive	С
Min recommended power (Hp - kW):	15 - 11		
Max recommended power (Hp - kW):	40 - 30		
Max power allowed (Hp - kW):	50 - 37		
Max speed (km/h - mph):	59 - 37		
Hull storage (m - fi)			
Length:	3.63 - 11'11"	Height:	0.69 - 2'3'
Width:	1.24 - 4'1"	Hull angle (°):	22.0
Folded boat dimensions (m - fi)			
Length of 1st bag:	-	Length of 2nd bag:	-
Width of 1st bag:	-	Width of 2nd bag:	-
Height of 1st bag:	-	Height of 2nd bag:	-

Equipments

Hull	Buoyancy tube	
 V-shaped polyester hull 	 Strongan[™] fabric 	
 Moulded non-slip deck 	 Easy Push valves 	
 Bow locker 	• Handrail	
• 1 bow D-ring	 2 Swivel oarlocks 	
 4 integrated lifting points 	 Broad rubbing strip 	
 1 stainless steel cleat 	• 2 oar rests	
 Fuel tank securing system 	 2 stainless steel tow rings 	
 Aluminium engine mounting plate 	 2 carrying handles 	
• 1 bailer	Cone reinforcers	
	 Removable buoyancy tube 	

Standard Equipment

- "Quick Release" upholstered removable thwart (dual position)
- Paddles
- Foot pump
- Repair kit
- Owner's manual